



型号: STP35	输出功率: 0.25KW
扬程: 8M	流量: 9.6M ³ /h water flow
电压: 220-240V	电流: 1.6A
口径: 50mm water connection	转速: 2900r/min
防护等级: IP55	电容: 7uF/450V
电机内置热保护器:自动复位	



型号: STP50	输出功率: 0.25KW
输入功率: 0.37KW power input	扬程: 11M
流量: 13M ³ /h	电压: 220-240V
电流: 2.0A	口径: 50mm
转速: 2900r/min	防护等级: IP55
电容: 7uF/450V	电机内置热保护器:自动复位



型号: STP75	输出功率: 0.37KW
输入功率: 0.55KW	扬程: 10.5M
流量: 14.4M ³ /h	电压: 220-240V
电流: 3.2A	口径: 50mm
转速: 2900r/min	防护等级: IP55
电容: 7uF/450V	电机内置热保护器:自动复位



塑料叶轮—环保安全

耐磨 工程塑料 更加坚固，环保安全

COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT, COPY NEW DESIGN TO REDUCE WATER LEAK EFFECT

DESIGN, USE IS MORE STABLE, USE IS MORE STABLE, USE IS MORE STABLE, USE IS MORE STABLE, USE IS MORE STABLE





进水口



出水口